

PORTABLE UTILITY LIGHTS

LIGHT SELECTION CHART & ILLUMINATION LEVELS

LIGHT SOURCE:		INCANDESCENT		QUARTZ HALOGEN		FLUORESCENT		METAL HALIDE	
# OF LIGHTHEADS		1	2	1	2	1	2	1	2
MAX. WATTAGE		300	600	500	1,000	55	110	100	200
MAX. LUMENS		3,700	7,400	11,000	22,000	3,000	6,000	9,000	18,000
AVG. BULB LIFE (HRS.)		2,000		2,000		10,000		15,000	
WIRE GUARD INCLUDED		Yes		Yes		Yes		Yes	
BULB INCLUDED		No		Yes		Yes		Yes	
LIGHT SOURCE ILLUMINATION LEVELS									
Measured Footcandles & Distance from Light Source (open area)	5' ft.	44.9	82.6	74.4	137.3	20.0	35.8	562.0	890.0
	10' ft.	20.8	38.9	36.1	65.9	8.7	14.8	148.1	244.1
	20' ft.	7.8	14.3	13.2	24.6	3.1	5.1	66.5	113.3
	30' ft.	4.0	6.9	6.6	12.3	1.7	2.5	47.1	68.7

FEATURES:

- Yellow & black powder coating finish.
- 15' long 18/3 SJT, 120V cordset with grounded plug.
- Shades will swivel 300° horizontally and 210° vertically.
- On/Off switch on each lighthouse.



4 TYPES OF LIGHT SOURCES:



INCANDESCENT

Uses commonly available and inexpensive, standard (R-40 or PAR) incandescent bulbs up to 300 watt flood lights.



QUARTZ HALOGEN

High light output from weatherproof aluminum die-cast light heads - uses 500 watt bulbs (included).



FLUORESCENT

Uses compact, low energy use, long life 55 watt Fluorescent bulb (included) - shade remains Cool-to-the-Touch.



METAL HALIDE

Longest lamp life - highest light output - lowest energy usage per lumens produced - uses 100 watt metal halide HID lamp (included).

6 TYPES OF BASES / MOUNTS:


PEDESTAL BASE

- 16 ga. round steel tube construction
- Height adjustable from 5'-6" to 8'-6" high
- 18" heavy duty steel base




CART BASE

- 16 ga. round steel tube construction
- Height adjustable from 5' to 8' high
- 10" diameter solid rubber wheels



TRIPOD BASE

- 20 ga. round steel tube construction
- Height adjustable from 3' to 6'-6" high
- Base covers 46" diameter area



FLOOR BASE

- 12 ga. steel base
- Handle included
- Base covers 16" diameter area



CLAMP-ON MOUNT

- Clamp secures lighthouse to most surfaces up to 3"



MAGNET MOUNT

- 210 lb. magnetic strength
- 1/4" steel arm
- Extends 6" from mounting surface



PORTABLE UTILITY LIGHTS

QUARTZ HALOGEN - SERIES



BASE TYPE	# of Lights	UPC CODE 686334	MODEL	WT. (LBS.)	LIST PRICE
PEDESTAL	1	479868	P-QH-1	36	232
	2	479875	P-QH-2	41	289
CART	1	479912	C-QH-1	32	300
	2	479882	C-QH-2	37	357
TRIPOD	1	480048	T-QH-1	14	130
	2	480055	T-QH-2	19	187
FLOOR	1	480116	F-QH-1	9	137
CLAMP	1	480154	CP-QH-1	8	108
MAGNET	1	480192	M-QH-1	7	119



All Models are shipped in ONE Carton



METAL HALIDE - SERIES



BASE TYPE	# of Lights	UPC CODE 686334	MODEL	WT. (LBS.)	LIST PRICE
PEDESTAL	1	480000	P-MH-1	38	657
	2	480017	P-MH-2	45	1094
CART	1	479943	C-MH-1	34	726
	2	479950	C-MH-2	41	1162
TRIPOD	1	480086	T-MH-1	16	555
	2	480093	T-MH-2	23	992
FLOOR	1	480130	F-MH-1	11	562
CLAMP	1	480178	CP-MH-1	10	533
MAGNET	1	480215	M-MH-1	9	544



PORTABLE UTILITY LIGHTS

INCANDESCENT - SERIES



BASE TYPE	# of Lights	UPC CODE 686334	MODEL	WT. (LBS.)	LIST PRICE
PEDESTAL	1	479967	P-INC-1	35	227
	2	479974	P-INC-2	39	295
CART	1	479899	C-INC-1	31	295
	2	479905	C-INC-2	35	363
TRIPOD	1	480024	T-INC-1	13	125
	2	480031	T-INC-2	17	193
FLOOR	1	480109	F-INC-1	8	130
CLAMP	1	480147	CP-INC-1	7	102
MAGNET	1	480185	M-INC-1	6	113

All Models are
shipped in
ONE Carton

FLUORESCENT - SERIES



BASE TYPE	# of Lights	UPC CODE 686334	MODEL	WT. (LBS.)	LIST PRICE
PEDESTAL	1	479981	P-FL-1	35	300
	2	479998	P-FL-2	39	431
CART	1	479929	C-FL-1	31	369
	2	479936	C-FL-2	35	499
TRIPOD	1	480062	T-FL-1	13	198
	2	480079	T-FL-2	17	329
FLOOR	1	480123	F-FL-1	8	204
CLAMP	1	480161	CP-FL-1	7	175
MAGNET	1	480208	M-FL-1	6	187



Note: All FL-Series units include wire guard (not shown).



HEAVY DUTY PORTABLE UTILITY LIGHTS

CART LIGHT STAND WITH GFCI

- Upright adjust from 5' to 8' high.
- 10" diameter rubber wheels.
- 15' all-weather, water and oil resistant SJTW 18/3 cordset and molded NEMA 5-15 plug.
- Weatherproof electrical box with a 15 amp GFCI duplex receptacle.



CART LIGHT STAND WITH GFCI

PUL-1000Q-CD

TRIPOD LIGHT STAND

- Square 12 ga. steel tubing construction.
- Adjustable legs fold up for storage, fold flat for sand bagging or can be set and locked at 6", 12", 18" or 24" ground clearances.
- Height adjustable from 5' to 11' high.
- Safety stop mechanism, at full extension, prevents the mast from being pulled out of the base.
- 15' all-weather, water and oil resistant SJTW 18/3 cordset and molded NEMA 5-15 plug.



TRIPOD LIGHT STAND

PUL-1000Q-TC



PUL-2000Q-TC

QUARTZ HALOGEN LIGHTHEADS

- 500 watt weatherproof die cast aluminum lightheads with 15' long, 3-conductor cord & plug. Quartz Halogen Lamps, impact resistant lens, on-off switch & OSHA approved wire guards included with each lighthead.

UPC CODE 686334	MODEL	BASE TYPE	BULBS	WATTS	VOLTS	MAX LUMENS	AVE BULB LIFE (HRS)	SHIPPING WT. (LBS.)	LIST PRICE
446785	PUL-1000Q-CD	CART	500W Qtz. Halogen	1000	120	22,000	2,000	50	601
446839	PUL-1000Q-TC	TRIPOD						41	635
446846	PUL-2000Q-TC	TRIPOD		2000	44,000	45	858		

COMMERCIAL DUTY PORTABLE UTILITY LIGHTS



CL 300 (Incandescent - Clamp-On Model)

- Ceramic socket will accept incandescent bulbs A-19, R-40 or PAR bulbs up to 300 watt. Fixture will also accept infrared heat lamps up to 250 watt (*Bulb not included).
- 8' long - 18/3 SPT cordset with NEMA 5-15 plug.



UPC CODE 686334	MODEL	BASE TYPE	BULBS	MAX. WATTS	VOLTS	MAX LUMENS	AVE BULB LIFE (HRS)	SHIPPING WT. (LBS.)	LIST PRICE
445078	CL-300	CLIP-ON	300W Incandescent	300	120	11000	2000	3	48

