


CUSTOMER	ı	DATE:
PROJECT		
LOCATION		
ARCHITECT		
ENGINEER		
CONTRACTOR		
SUBMITTED BY		
APPROVED BY		
APPROVED BY		



SUBMITTAL DATA SHEET									
QTY	TAG	MODEL	WATTAGE	VOLTS	PHASE	AMPS	FINISH	ACCESSORIES	ACCESSORIES
NOTES/SPECIAL INSTRUCTIONS:									

## **Product Specifications**

### **CONSTRUCTION:**

Radiant Ceiling Panels shall be made of highest quality steel casing. Front panel shall be painted with textured powder coated finish. Electric Resistance element is fixed between dielectric material and insulation. Two inches of insulation is compressed to one inch by back panel to minimize upward heat loss and radiant efficiency. Radiant panels shall have 36" pre-wired flexible cable for easy installation and wiring connections. CP Series is 20 Gauge metal. Made in U.S.A.

#### **INSTALLATION:**

CP Series shall be designated as 2x2 or 2x4 size. All panels are 1" thick. The size shall be nominal dimension to be manufactured to fit drop ceiling systems. Standard units will fit regular "T" Bar frame. For regular or trim line or other frame sizes, special construction is required. RCP Series shall be used in recess mounting applications. RCP Series shall be 2" less in width to recess between nominal 24" center ceiling joists. RCP Series shall be complete with recess frame for finished construction.

#### **ACCESSORIES:**


Surface mounting frames shall be optional for surface mounting the CP Series, and are Aluminum mill finish. Frames can be painted white to match panel.

#### **OPTIONS:**

Silk-screening the exposed surface to match ceiling tiles is available, as well as silicone sealed metal parts for high humidity applications. **NOTE:** 

Add \$25.00 Net for each unit for application of Silicone to ceiling panel for high humidity areas.

- 20 Gauge steel casing
- Powder coated with high heat paint. White finish
- Custom screen printing available to match existing accoustical ceiling panels
- 2" Thick insulation compacted inside unit for minimal heat loss from the back of the unit
- Models for surface mounting or recessed mounting applications
- Recess frame included with RCP models
- Optional surface mounting frame available for CP models
- 36" Pre-wired flex conduit wip for easy installation



## **Product Description**

For Surface Or Recessed Installation, Radiant Ceiling Panels radiate energy like the solar radiation which warms us, heats objects, not the air. With no moving parts, these heating panels create gentle warmth and toasty comfort.

Radiant Ceiling Panels provide a low surface temperature and broad heat distribution. Clean, gentle comfortable heat that is ideal for offsetting perimeter heat loss or neutralizing downdrafts over glass. These versatile and flexible panels may be used virtually anywhere in homes, schools, hospitals, motels and a broad variety of other commercial or industrial installations.

## CP Series "T" Bar & Surface Mounted

MFG CATALOG NUMBER	MFG MODEL NUMBER	WATTS	BTUs	AMPS	VOLTS	WT. (LBS)								
Dimensions: 2' x 4' (Nominal) x 1"														
04587102	CP805			2	208									
04587202	CP125	500	1707	4.2/2.1	120/240	20 lb.								
04587302	CP705			2	277									
04587402	CP807			4	208									
04587502	CP127	750	2560	6.3/3.1	120/240	20 lb.								
04587602	CP707			3	277									
	Dimens	ions: 2' x	2' (Nomi	nal) x 1"										
04587702	CP802	250		1	208									
04587802	CP122		250	250	250	250	250	250	250	250	250	853	2.1/1.0	120/240
04587902	CP702			.9	277									
04588002	CP803	375		2	208									
04588102	CP123		1280	3.1/1.6	120/240	13 lb.								
04588202	CP703			1	277									
04591002 SF400 Surface Frame for 2' x 4' Panels (CP only)						10 lb.								
04590902	SF200 Surface Frame for 2' x 2' Panels					6 lb.								

SURFACE FRAMES (FOR CP MODELS ONLY)				
MODEL	WEIGHT			
SF200	6 LB			
SF400	10 LB			

# RCP Series Frame in Ceiling Mounted

MFG CATALOG NUMBER	MFG MODEL NUMBER	WATTS	BTUs	AMPS	VOLTS	WT. (LBS)				
Dimensions: 2' x 4' (Including Recessing Frame)										
04588302	RCP805	500		2	208	30 lb.				
04588402	RCP125		1707	4.2/2.1	120/240					
04588502	RCP705			2	277					
04588602	RCP807			4	208					
04588702	RCP127	750	750	750	750	750	0 2560	6.3/3.1	120/240	30 lb.
04588802	RCP707			3	277					
Dimensions: 2' x 2' (Including Recessing Frame)										
04588902	RCP802	250			1	208				
04589002	RCP122		853	2.1/1.0	120/240	19 lb.				
04589102	RCP702			.9	277					
04589202	RCP803			2	208					
04589302	RCP123	375	1280	3.1/1.6	120/240	19 lb.				
04589402	RCP703			1	277					